



### Product Identification

340221

- ONIX PLUS 2 in 1

### Definition and Application

- OLI exposed cistern which can be fixed in wall (medium-low position) or directly in the pan (close-couple)
- Ideal to replace ceramic cisterns

### Technical Features

Millimetres measures

- Dual flush 6/3 litres (adjustable to 4/2 in the outlet valve)
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Other versions compliant with:KIWA
- EN 14055 CL1
- 137mm thickness
- Water supply connection – Lateral and back (a bended connection pipe or flexible hose it's needed)
- White PS material
- "A" class for the water efficiency in compliance with the ANQIP authority requirements
- Acoustic and anti-condensation internal lining

### Accessories

#### Medium low level installation

- 1 Flush pipe Ø50/40
- 1 Seal for flush pipe Ø40
- 1 Rubber seal
- 1 Washer
- 2 Suspension fasteners
- 2 Bushing 6mm
- 2 Screws Ø4,2X25

#### Close couple installation

- 1 Sponge washer
- 2 Fixers
- 2 Screws M6X70
- 2 Plastic nuts

## Warranty

Five (5) years warranty according to the general selling terms, starting from the purchase date of the product.

If the product is not correctly installed the warranty is not valid

## Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)